



RESPONSE MONOBLOC FILLER

Response Monobloc filler

Adelphi's Response Monobloc Filler provides many advantages for customers compared with traditional inline packaging systems.

Key features and benefits:

- Capable of filling 3ml to 250ml containers
- Space-saving design
- Ten-minute strip down time
- Response volumetric filler fill-accuracy +/- 0.25%
- Hygienic stainless steel construction; all wetted parts are 316 stainless steel
- Quick and easy to change parts from one fill-size container to another
- Easy-to-use intuitive HMI touch screen controls for your operator
- Designed to effectively handle liquids, oils, creams, pastes and solids in suspension
- Speed of operation in the region of 35 per minute
- Reduced labour costs

The Response Monobloc Filler can incorporate the following elements to give a complete turnkey packaging line:

- In-feed table
- Bottle blower
- Filler
- Automatic cap placement
- Capper
- Labeller
- Collection table



	Specification
Accuracy	±0.25%
Output (per minute)	Dependent on fill volume
Height without hopper / tank	1850 mm
Depth	860 mm
Width without conveyor	1152 mm
Weight	265 kg (plus Response base unit and hopper)
Air consumption per cycle	7.5 litres at 6 bar
Volume range	5 ml – 250ml
Electrical consumption	3 phase with Neutral, 415VAC, 16A supply

The Response Monobloc Filler has been designed to work with our Adelphi Response Volumetric Filler, but it can also be configured to incorporate fillers from other suppliers.